PRODUCT DATA SHEET

DAB-300MP • 701417





PRODUCT DETAILS

The pump is a self-priming surface mounted jet pump and has a suction capability of up to 8m.

APPLICATIONS

- Domestic installations where a suction lift is required
- Pressure boosting, irrigation and wash down
- Designed for pumping from tanks, rivers and dams.

FEATURES

- Pressure switch with adjustable differential
- Pressure gauge
- Self priming centrifugal pump with excellent suction capability
- 240V single phase TEFC motor with in-built auto reset thermal overload to prevent pump from damage
- A pressure tank is required


TECHNICAL DATA

MATERIALS IN CONTACT WITH DRINKING WATER					
PUMP					
PUMP BODY	GJL 200 Cast Iron				
IMPELLER	Glass reinforced Noryl				
JET, VENTURI, DIFFUSER	Glass reinforced Noryl				
MECHANICAL SEAL	Carbon Ceramic Nitrile				
O RINGS	Nitrile				


SPECIFICATIONS	
RATED POWER (KW)	2.2 (3hp)
MAX. FLOW [LPM]	185
MAX. HEAD [M]	51
PORTS	40mm x 32mm (1-1/2"x1-1/4")BSP
START PRESSURE (BAR)	1.9
STOP PRESSURE (BAR)	3.9
VOLTS (V)	240
CARTON DIMENSIONS	660mm L x 236mm W x 267mm H
WEIGHT (KG)	31.5




CURVE



DIMENSIONS





MODEL	A	В	С	E	F	G	ΙØ	Н	H1	DNA GAS	DNM GAS
JET 300 M	595	214	151	282	20	160	11	235	175	1½"	1¼"

WARRANTY / CERTIFICATIONS





