# PRODUCT DATA SHEET

#### DAB-DP151M • 701508



# **PRODUCT DETAILS**

The pump is a self-priming surface mounted deep well pump and has a suction capability of up to 27m with seperately supplied injector kit.

### **APPLICATIONS**

- Domestic installations where a suction lift is required
- Pressure boosting, irrigation and wash down
- Designed for pumping from wells and from rivers and dams using offset.

# FEATURES

• 240V single phase TEFC motor with in-built auto reset thermal overload to prevent pump from damage



# **TECHNICAL DATA**

MATERIALS IN CONTACT WITH DRINKING WATER												
PUMP												
PUMP BODY	GJL 200 Cast Iron											
IMPELLER	Glass reinforced Noryl											
JET, VENTURI, DIFFUSER	Glass reinforced Noryl											
MECHANICAL SEAL	Carbon Ceramic Nitrile											
O RINGS Nitrile												


SPECIFICATIONS	
RATED POWER (KW)	1.1 (1.5hp)
MAX. FLOW [LPM]	58
MAX. HEAD [M]	60
PORTS	32mm x 25mm (1-¼"x1")BSP
VOLTS (V)	240
CARTON DIMENSIONS	427mm L x 246mm W x 307mm H
WEIGHT (KG)	28.5







HYDRAULIC DATA (n ~ 2800 1/min.)													
		DEEP	Discharge pressure in bar										
TYPE PUMP	TYPE Ejector		3	3.5	4	4.5	5	5.5	6	6.5	7		
	Locorom	oconion			Cap	pacit	y tab	le in	l/h				
		9	3470	2890	2220	1500	750	-	-	-	-		
	E 20	12	3110	2510	1850	1100	300	-	-	-	-		
		15	2710	2100	1380	640	-	-	-	-	-		
		18	2360	1700	950	-	-	-	-	-	-		
		15	2800	2330	1830	1350	900	520	_	_	_		
DP 151 M - T	E 25	18	2530	2050	1550	1090	680	300	-	-	-		
		21	2280	1800	1300	860	470	-	-	-	-		
	E 30	21	1820	1650	1410	1160	910	700	520	_	_		
		24	1680	1520	1260	1020	780	580	420	-	-		
		27	1550	1360	1110	880	680	490	330	-	-		

#### DIMENSIONS







MODEL	A	В	C	DNA Gas	DNE GAS	DNM GAS	E	G	H	H1	H2	١ø	x	у	z
DAB-151	388	210	50	1" ¼	1"	1"	197	145	255	53	108	11	1"G	1"G	1"¼ G

#### WARRANTY / CERTIFICATIONS

